

Fig 1







FIG. Z




F16.3





•



F19.6

HEE	Side	P **	Test 1	Test 2	Test 3	
SIN		Marked on Board	Deflection @ 500 lbs,in.	Deflection 1 Board  @ 500 lbs,in.	Max Load, lbs/Deflection/Failure	
1	Α	12-94	1.975	2.282	1527 lbs/6.385"/simple tension	
1	В	12-94	2.002	2.034		
2	A	12-94	2.378	2.308	1648 lbs/7.760"/full deflection reached with no failure	
2	В	12-94	2.508	2.271		
3	A	12-94	2.157	2.124	1652 lbs/6.844*/simple tension	
3	В	12-94	1.996	2.051		
4	A	11-94	2.002	2.174	1774 lbs/7.438"/full deflection reached with no failure	
4	В	11-94	2.005	2.112		
5	A	11-94	1.594	N/A	2147 lbs/6.785"/cross-grain tension failure	
5	В	11-94	1.810	N/A		
6	A	11-94	1.914	N/A	1009 lbs/4.275"/simple tension	
6	В	11-94	2.081	N/A		

Fig. 7

Figure 8

COMPARISON RESULTS				
	Pinned	Solid	Laminated	
Modulus of Elasticity	2.0 x 10 <sup>6</sup>	$1.8 \times 10^6$	2.15 x 10°	
Flexural Stress	2,600 psi	2,200 psi	2,900 psi	
Horizontal Sheer Stress	120 psi	90 psi	145 psi	

## Figure 9

FAILURE RESULTS						
Type of Board	Average Failure Load (lbs)	Comments				
Pinned	2,700 psi	One member out of three fail first				
Solid	2,200 psi	Whole unit fails				
Laminated	2,400 psi	Whole unit fails				

## Figure 10

DEFLECTION RESULTS					
Type of Board (7 ft span)	Deflection @ 50 psf Load (in)	OSHA Allowable Deflection (in)			
Pinned	0.73	1.4			
Solid	0.81	1.4			
Laminated	0.73	1.4			